GYSPOT EXPERT 400

Ref. 058859



Dedicated for various dent pulling and straightening body shop operations, the GYSPOT EXPERT 400 is a high spec machine able to deliver up to 4500A of power. The welding current and welding duration are set separately for a more accurate control of the impact to galvanise and particularly thin steel sheet.

EQUIPMENT DESIGNED FOR PROFESSIONALS THAT REQUIRE COMPLETE CONTROL OF THEIR DENT PULLING PROCESS.

Designed to be connected to a 400V - 2ph power source with a 16A slow blow fuse, the GYSPOT EXPERT 400 can be used in two different modes:

✓ A MANUAL mode, where the operative can independently set the welding current and welding time to fit the requirements of a particular job/material thickness.

✓ A SYNERGIC mode: The machine will use the GYS Expert Engineers recommended settings. Simply select the tool to be used and the power is automatically set.

For extra control, two welding operations are available:

- ✓ Automatic operation: the Arc begins when the tool is in contact with the metal sheet.
- ✓ **Manual** operation: the Arc begins when the tool is in contact with the metal sheet and the trigger is pressed.



The EXPERT is designed to carry out multiple body shop tasks. The operative has the choice of 7 dedicated programs :



- Dent pulling operations
- · welding of wavy wire or pulling rings
- Dent Removal using copper stars
- Carbon electrodes for steel shrinking
- Welding of keys for lateral rods
- Welding of rings for earth fixing
- Welding of studs to fix earth and connection cables to vehicle

SUPPLIED WITH ALL STANDARD ACCESSORIES REQUIRED TO OPERATE



1 GUN WITH TRIGGER

ref. 057524 - 2 m - Ø 70 mm²



1 SPOTTER BOX PRO

ref. 050075



Cable length:

earth : 2 m

ref. 059207 - 3 m - Ø 70 mm²

power supply: 8 m



Trolley UNIVERSAL 800 ref. 051331

Trolley SPOT 1600 ref. 051348

50/60hz	- AM-	APPARENT POWER (VA)	I RMS	I _{2max}	U ₂			DETECTION	cm cm	₽ kg	
		` ,							CIII	ĸy	
400 V, 2ph	16 A (D)	19.4kVA	3200 A	4500 A	7,4 V	ОК	ок	AUTO / MANUAL	22,5 x 36 x 23,5	31,5	