



**LED FLOOD LIGHT (PF 0.6)**  
\*\*\*<< ECO SERIES >>\*\*\*

**APPLICATION**

- Ideal for Parking Areas, Gardens, Billboard, Facade Lightings, and All Commercial or Residential Areas.

**FEATURES**

- Long Life LED Chips (15,000Hrs).
- Operating Temperature -20° C ~ 50° C.
- Aluminium Die-Casting and Non-Corrosive Housing.
- UV-Proof Polycarbonate Material Diffuser.
- No External Driver Required (DOB) and High Energy Efficiency.



**10 + 4KV SURGE PROTECTION**  
(Starts from 100W/150W/200W)



MODEL	POWER (W)	CCT (KT)	LUMEN (LM)	SIZE L x W x H (mm)	NET WEIGHT (kg)	PACKING
BSFL-3030-1	30W	3000/6500	3000	159 x 182 x 29	0.5	20/CTN
BSFL-3050-1	50W	3000/6500	5000	184 x 219 x 29	0.9	20/CTN
BSFL-3100-1	100W	3000/4000/6500	10000	238 x 274 x 29	1.7	10/CTN
BSFL-3150-1	150W	3000/6500	15000	272 x 293 x 31	2.8	10/CTN
BSFL-3200-1	200W	3000/4000/6500	20000	316 x 344 x 31	3.3	10/CTN

