

**Solar LED Street Light
200W / 400W / 600W
with Monocrystalline
Silicon Solar Panel**

APPLICATION
Parking Areas, Stadiums,
Pathway, Garden, Commercial
and Residential Areas.

FEATURES

- Solar charging.
- Charging time 4 - 8 hours.
- Working time 10 - 12 hours.
- Easy to install, no complicated wiring required.
- There is a light indicating the remaining battery.
- Remote control adjust the brightness as needed remote control distance of 10 meters.
- The remote can set the timer to turn off automatically, there are 3/5/8 hours.
- IP67 waterproof and rainproof.
- Recommended installation height 3m-5m for 200W; 4m-6m for 400W; 5m-7m for 600W



LUMINAIRE SPECIFICATION

- Color Temperature : 6500K Day Light
- Color Rendering Index : ≥ 70
- Lifetime : 30,000Hrs
- Beam Angle : $140^\circ \times 70^\circ$
- Voltage : DC 3.2V
- Working Environment : $-10^\circ\text{C} \sim 40^\circ\text{C}$
- Material : Cast Iron + PC
- Battery Type : Lithium-ion
- Recommended installation height : 3m – 5m (200W)
4m – 6m (400W)
5m – 7m (600W)



Model	Power (W)	CCT (K)	Lumen (lm)	Battery Capacity	Solar Panel (L x W x H)mm	Charging Power	Lamp Size (L x W x H)mm	Net Weight	Packing
BSSLSL-1200	200W	6500	2200	20Ah	450 x 350 x 17	6V/25W	490 x 215 x 60	3.9 kg	1/CTN
BSSLSL-1400	400W	6500	4400	30Ah	600 x 350 x 17	6V/35W	490 x 215 x 60	4.8 kg	1/CTN
BSSLSL-1600	600W	6500	6600	40Ah	700 x 350 x 17	6V/45W	700 x 255 x 60	6.0 kg	1/CTN

Remark *: Pole / Arm, solar panel & bracket all included