


BSLight

Backlit LED DOB Down Light (Surface)

 **APPLICATION**
Ideal for commercial or residential place,
office, hotel, meeting room & etc.



SPECIFICATION

Type	▶ Backlit DOB
I/P Voltage	▶ AC 220 - 240V
Power Factor	▶ > 0.5
Power Efficiency	▶ 90 lm/w
CRI	▶ ≥ 80
Housing Materials	▶ Round Type (PP Fireproof) ▶ Square Type (PP Fireproof)
Diffuser Plate	▶ PS
Life Time	▶ 15,000 Hrs



ROUNDTYPE

Model	Power (w)	CCT (K)	Lumen (Lm)	Lamp Size (mm)	Beam Angle	Packing
BS-1060R-SF-6"	12 W	3000K/4000K/6500K	960	Ø175 x 35	120°	30/ctn
BS-1080R-SF-8"	18 W	3000K/4000K/6500K	1440	Ø225 x 35	120°	30/ctn
BS-1099R-SF-12"	30 W	3000K/4000K/6500K	2400	Ø289 x 35	120°	20/ctn

SQUARETYPE

Model	Power (w)	CCT (K)	Lumen (Lm)	Lamp Size (mm)	Beam Angle	Packing
BS-1060S-SF-6"	12 W	3000K/4000K/6500K	960	175 x 175 x 35	120°	30/ctn
BS-1080S-SF-8"	18 W	3000K/4000K/6500K	1440	225 x 225 x 35	120°	30/ctn
BS-1099S-SF-12"	30 W	3000K/4000K/6500K	2400	289 x 289 x 35	120°	20/ctn