



4600 Staticide® Ultra Floor Finish

High quality, high performance

No other ESD floor finish can match Staticide® Ultra Floor Finish for electrical properties, physical longevity, and gloss. The formula features superior abrasion resistance and durability, fortifying floors with a shiny, ESD-safe, long-lasting protective layer for 12 to 24 months.

By maximizing stripping cycles, companies can decrease costs by eliminating annual labor fees and production shutdowns. Its reliability makes Staticide Ultra an ideal choice for companies implementing a static protection facility complying to ANSI/ESD S20.20.

The water-based formula is UL-listed for slip resistance, RoHS and REACH-compliant, biodegradable, non-flammable, and free of formaldehyde, phthalates, alkalis, acids, and ammonia.

Directions:

Clean floor and apply two to three thin coats of floor finish with a dedicated lint-free mop. Wait a minimum of one hour between coats. See application instructions for details.

Maintenance:

Sweep or dust mop daily. Do not use sweeping compound. Periodically clean with a 1:1 dilution of water and floor finish. Apply a thin top coat of floor finish every 4 – 6 weeks. For heavy cleaning, use the 4100 Restorer Cleaner. Consult maintenance procedure for details and precise instructions.

Product# 4600-1: 1-gallon pail

Product# 4600-5: 5-gallon pail

Product# 4600-2: 54-gallon pail

Ideal for the following applications:

- Electronics manufacturing and assembly
- Sensitive device manufacturing
- Medical and cleanroom facilities
- ESD workspaces
- Static-sensitive warehousing and data centers

FEATURES

- ✿ Suitable for floor specifications outlined in ANSI/ESD S20.20
- ✿ Surface Resistance: $10^7 - 10^9$ ohms @ 100v and 12rH
- ✿ VOC : < 4%
- ✿ Solids: $22\% \pm 5\%$
- ✿ Coverage: 1500 - 2000 square feet per gallon
- ✿ UL listed for slip resistance
- ✿ Use on VCT, linoleum, or ceramic tile
- ✿ Strip cycle is 12 - 24 months
- ✿ Made in USA



ACL Staticide®

840 W. 49th Place · Chicago, IL 60609
800.782.8420 · 847.981.9212 · fax 847.981.9278
info@aclstaticide.com · www.aclstaticide.com



ACL, Inc. has been certified by
DQS Inc. to ISO-9001 : 2015
Certificate NO. 10002746