

Edenaire New Generation Portable Dehumidifier



- Microcomputer digital intelligent control
- Digital humidity indication
- Auto control from 40% to 80% humidity
- Auto display from 35% to 90% humidity
- Automatic defrosting for protection
- Delayed startup for protection
- Overflow protection alarm
- 0-24 hours programmable timer
- Auto shut off when tank is full
- Permanent drainage option
- Universal wheels easy for moving

Outstanding Features:

- ❖ Inner thread copper tube: 50% more efficiency, 30% moisture removal improved
- ❖ Self clean titanium heat exchanger: Essential part of the unit, 15% efficiency improved

Model	ED2042X
Moisture removal at 30°C & 80% RH	20L/Day
Power source	220-240Vac/1Ph/50Hz/1.5A
Operating temperature	5-32°C
Recommended room size	15-50m ²
Rated power	330W
Refrigerant	R134a
Drainage	Bucket (4L) or drain pipe
Noise level	≤40db(A)
Speed mode	Quiet/laundry drying
0-24hours Timer, Auto Defrost	Yes
Operation panel	Electronic button
Compressor 3min delay protection	Yes
Bucket full alarm & protection	Yes
Universal castors & swing	Yes
Net weight	15.5kg
Net dimension(mm)	590H x 350W x 215D mm

0210k



To-Morrow's Technologies Today

ENMARK (M) SDN BHD 166374-H
 8 Jalan Tembaga SD5/2A
 Bandar Sri Damansara
 52200 Kuala Lumpur, Malaysia
 GST ID No: 000142524416

Tel: +60-3-62723232
 Fax: +60-3-62758069
 Email: enmark1@live.com or
sales@enmarkcontrol.com
www.enmarkcontrol.com