

Edenaire New Generation Portable Dehumidifier



Technical Feature

- Microcomputer digital intelligent control
- Digital humidity indication
- Air purification via inbuilt ionizer
- Inbuilt uv lamp sterilize the bacteria in the air
- Auto control from 40% to 80% humidity
- Auto display from 35% to 90% humidity
- Automatic defrosting for protection
- Delayed startup for protection
- Overflow protection alarm
- 0-24 hours programmable timer
- Auto shut off when tank is full
- Permanent drainage option
- Universal wheels easy for moving

| | |
|-----------------------------------|---|
| Model | ED2042E |
| Moisture removal at 30°C & 80% RH | 20L/Day |
| Power source | 220-240Vac/1Ph/50Hz/2A max |
| Operating temperature | 5-32°C |
| Applicable area | Nominal 30m ² , maximum 35m ² x 3m height |
| Rated power | 330W |
| Maximum power | 440W |
| Refrigerant | R134a |
| Drainage | Bucket (4L) or drain pipe |
| Noise level | ≤40db(A) |
| Speed mode | Quiet/laundry drying |
| 0-24hours Timer, Auto Defrost | Yes |
| Operation panel | Electronic button |
| Compressor 3min delay protection | Yes |
| Bucket full alarm & protection | Yes |
| Universal castors & swing | Yes |
| Net weight | 15.5kg |
| Net dimension(mm) | 590H x 350W x 215D mm |

0503e



To-Morrow's Technologies Today

ENMARK (M) SDN BHD 166374-H
 8 Jalan Tembaga SD5/2A
 Bandar Sri Damansara
 52200 Kuala Lumpur, Malaysia
 GST ID No: 000142524416

Tel: +60-3-62723232
 Fax: +60-3-62758069
 Email: enmark1@live.com or
sales@enmarkcontrol.com
www.enmarkcontrol.com