

R7247; R7248; R7249; R7476 Flame Amplifiers



Solid state plug-in units respond to flame detector signal and indicate presence of flame.

- Use with BC7000; R4140; R4075C,D,E; R4138C,D Flame Safeguard controls and appropriate flame detector and FSP5075A1, FSP5075A3 Flame Amplifier Modules

Approvals

Canadian Standards Association: Certified: File No. LR1620, Guide No. 140-A-2

Control Safety Devices: Acceptable (CSD-1)

Factory Mutual: Approved: Report No. 24181.01

Swiss Re: Acceptable

Underwriters Laboratories, Inc: Listed: File No. MP268, Guide No. MCCZ2

| Product Number | Flame Failure Response Time (sec) | Self Checking | Use With Flame Sensor | Use With Primary Safety Control | Comments |
|----------------|-----------------------------------|--------------------|--|--|---------------|
| R7247B1003/U | 2 to 4 sec | Ampli-Check | Gas: Rectifying Flame Rods C7004, C7005, C7007, C7008, C7009, Q179 Gas, oil, coal: Ultraviolet Flame Sensor C7012A, C | R4140; BC7000; R4075C,D,E; R4138C,D; FSP5075 | Color: Green |
| R7247C1001/U | 2 to 4 sec | Dynamic Self-Check | Gas, oil, coal: Ultraviolet Flame Sensor C7012E, F | R4140, BC7000, R4075C,D,E, R4138C,D; FSP5075 | Color: Green |
| R7247C1019/U | 2 sec max. | Dynamic Self-Check | Gas, oil, coal: Ultraviolet Flame Sensor C7012E, F | R4140; BC7000; R4075C,D,E; R4138C,D; FSP5075 | Color: Green |
| R7248A1004/U | 2 to 4 sec | None (standard) | Gas, oil, coal: Infrared (lead sulfide) C7015 | R4140; BC7000; R4075C,D,E; R4138C,D; FSP5075 | Color: Red |
| R7249A1003/U | 2 to 4 sec | None (standard) | Gas, oil, coal: Ultraviolet (Minipeeper) C7027, C7035 | R4140; BC7000; R4075C,D,E; R4138C,D; FSP5075 | Color: Purple |
| R7476A1007/U | 2 to 4 sec | Dynamic Self-Check | Gas, oil, coal: Adjustable Sensitivity Ultraviolet Flame Sensor C7076 | R4140; BC7000; R4075C,D,E; R4138C,D; FSP5075 | Color: Blue |
| R7476A1015/U | 2 sec max. | Dynamic Self-Check | Gas, oil, coal: Adjustable Sensitivity Ultraviolet Flame Sensor C7076 | R4140, BC7000, R4075C,D,E, R4138C,D; FSP5075 | Color: Blue |

R7259 Flame Safeguard Amplifiers

Solid state, plug-in units allow use of rectification, infrared and ultraviolet flame detections.

- Use with Q518, Q519 and W688A Flame Safeguard multi-burner modules and appropriate flame detector

Approvals

Canadian Standards Association: Certified: File No. LR95329-3

Underwriters Laboratories, Inc: Listed: File No. MP268, Guide No. MCCZ2

| Product Number | Flame Failure Response Time (sec) | Self Checking | Use With Flame Sensor | Use With Primary Safety Control | Comments |
|----------------|-----------------------------------|-----------------|---|---------------------------------|---------------|
| R7259A1000/U | 2 to 4 sec | None (standard) | Gas, oil, coal: Ultraviolet (Minipeeper) C7027, C7035 | Q518, Q519, W688A | Color: Purple |