

JET SEWER CLEANING HOSE





SPECIFICATION

Application: Standard Sewer cleaning vehicles and cleaning equipment's. Special construction for optimum cut and wears resistance. Bonded tube and cover. Hose are available in long lengths with a special cover resistant to microbiological degradation. Lightweight compared to conventional rubber alternatives and increased lifetime.

Temperature: from -40°C to +60°C

CONSTRUCTION

Tube: Thermoplastic Elastomer

Reinforcement: 2 braids of synthetic fibre

Cover: Orange color – polyurethane **Branding:** continuous "Thermoflex".

	0		0		Ø		24		N
CODE	Inside Diameter		Outside Diameter		Working Pressure		Burst Pressure		Bending Radius
	mm	Inch	mm	Inch	Bar	PSI	Bar	PSI	mm
16-OSJ-06	9.0	3/8	0.65	16.5	210	3000	525	7500	75.0
16-OSJ-08	12.0	1/2	0.88	22.4	210	3000	525	7500	100.0
16-OSJ-12	19.0	3/4	1.25	31.8	210	3000	525	7500	125.0
16-OSJ-16	25.0	1	1.525	38.7	210	3000	525	7500	160.0
16-OSJ-20	32.0	1 1/4	1.84	46.7	210	3000	525	7500	250.0