



STEAM HOSE

Radiator Hose 10 Bar



Application

Hardwall hose are made to withstand heat, vibration, pressure and cooling systems chemical to provide the flexible connection for coolant flow between the engine and the radiator.

Tube: Black color of EPDM blend compound. Heat resistance.

Cover: Black color of EPDM blend compound. Heat, abrasion and weather resistance.

Reinforcement: Multiple layers of high tensile synthetic cord.

Temperature: -30°C to 120°C

Nominal inch	I.D (mm)	O.D (mm)	Pressure (bar)		Weight (Kg/m)	Length (m)
			Working	Burst		
1"	25.4	35.0	10	30	0.517	1
1-1/8"	28.6	38.0	10	30	0.555	1
1-1/4"	31.8	42.0	10	30	0.684	1
1-3/8"	35.0	45.0	10	30	0.723	1
1-1/2"	38.1	48.0	10	30	0.768	1
1-5/8"	41.3	51.0	10	30	0.803	1
1-3/4"	44.5	55.0	10	30	0.958	1
1-7/8"	47.8	58.0	10	30	0.982	1
2"	50.8	62.0	10	30	1.098	1
2-1/8"	54.0	65.0	10	30	1.132	1
2-1/4"	57.0	69.0	10	30	1.354	1
2-3/8"	60.5	72.0	10	30	1.342	1
2-1/2"	63.5	75.5	10	30	1.494	1
2-5/8"	66.0	78.0	10	30	1.548	1
2-3/4"	70.0	82.0	10	30	1.634	1
2-7/8"	73.3	85.0	10	30	1.643	1
3"	76.2	88.0	10	30	1.725	1
3-1/2"	89.0	102.0	10	30	1.861	1
4"	102.0	114.0	10	30	1.854	1
4-1/2"	115.0	128.0	10	30	2.727	1
5"	127.0	140.0	10	30	2.997	1