

# ASHFLEX

## LPG/PROPANE GAS HOSE 20 BAR



The LPG (Liquefied Petroleum Gas) Hose is designed for the safe transfer of LPG, propane, butane, and their mixtures in domestic, commercial, and industrial applications.

### COMMON APPLICATION

The LPG (Liquefied Petroleum Gas) Hose is designed for the safe transfer of LPG, propane, butane, and their mixtures in domestic, commercial, and industrial applications.

### TYPICAL APPLICATIONS

- ✓ LPG transfer in industrial plants and gas distribution systems
- ✓ Connection of gas cylinders to domestic and commercial appliances
- ✓ Gas supply for heating, cooking, and industrial burners
- ✓ LPG delivery from tank trucks to storage tanks
- ✓ Portable gas equipment in construction and camping

### KEY FEATURES

**REINFORCEMENT**  
High strength synthetic fibre braided

**COVER**  
Orange color of EPDM blend compound. Abrasion, weather and burn resistance.

**INNER TUBE**  
Black color of NBR blend compound. LPG resistance.

**WORKING PRESSURE**  
Constant Pressure  
20 Bar / 300 PSI

**TEMPERATURE RANGE**  
-32°C to +80°C

**SAFETY FACTOR**  
3 : 1

### NOTE

LPG hoses must be used according to their rated pressure and temperature. Always ensure proper fittings and leak testing before operation. Avoid contact with sharp edges, flames, or excessive heat sources.

### SPECIFICATIONS

Part No.	ID		OD	Working Pressure		Burst Pressure		Length
	(inch)	(mm)	(mm)	(Bar)	(Psi)	(Bar)	(Psi)	(m)
ASH-LPH-2004	3/16"	4.8	11	20	300	60	900	100
ASH-LPH-2006	1/4"	6.4	14	20	300	60	900	100
ASH-LPH-2007	5/16"	7.9	16	20	300	60	900	100
ASH-LPH-2009	3/8"	9.5	18	20	300	60	900	100
ASH-LPH-2012	1/2"	12.7	21	20	300	60	900	100
ASH-LPH-2016	5/8"	16	26	20	300	60	900	100
ASH-LPH-2019	3/4"	19	29	20	300	60	900	100
ASH-LPH-2022	7/8"	22	32	20	300	60	900	100
ASH-LPH-2025	1"	25.4	36	20	300	60	900	100

Brand Reference: ASHFLEX LPG HOSE - ID 1/4" - W.P.20BAR/300PSI -