



# Cement Suction Hose 10 Bar



## Application

Hardwall hose used for suction of dry cement, sand, gravel, feed, seeds etc.

Tube: Antistatic black SBR blend compound. High abrasion resistance.

Cover: Black color of SBR blend compound. Abrasion and weather resistance.

Reinforcement: Multiple layers of high tensile synthetic cord and supported with helix wire.

Temperature: -20°C to +80°C

Nominal inch	I.D (mm)	O.D (mm)	Pressure (bar)		Weight (Kg/m)	Length (m)
			Working	Burst		
1-1/2"	38.1	52.0	10	30	1.389	30
2"	50.8	67.0	10	30	2.203	30
2-1/2"	63.5	84.0	10	30	3.300	30
3"	76.2	97.0	10	30	3.962	30
3-1/2"	88.9	110.0	10	30	4.152	30
4"	101.6	124.0	10	30	5.711	30
5"	127.0	150.0	10	30	6.815	30
6"	152.0	176.0	10	30	8.687	30
8"	203.2	230.0	10	30	13.261	30
10"	254.0	284.0	10	30	18.141	12
12"	304.8	336.0	10	30	24.941	12
14"	355.6	390.0	10	30	30.149	12
16"	406.4	446.0	10	30	35.409	12