

# ASHFLEX

## PLASTER / CEMENT HOSE 40 BAR



The Plaster / Cement Hose is a heavy-duty, abrasion-resistant hose designed for the conveyance of wet or dry cement, plaster, grout, and other high-density construction materials.



### COMMON APPLICATION

The Plaster / Cement Hose is a heavy-duty, abrasion-resistant hose designed for the conveyance of wet or dry cement, plaster, grout, and other high-density construction materials.



### TYPICAL APPLICATIONS

- ✓ Transfer of wet or dry cement mixtures
- ✓ Plaster and grout pumping in construction projects
- ✓ Shotcrete delivery in tunneling and mining operations
- ✓ Concrete spraying in civil engineering works
- ✓ Material handling in building and repair works



### KEY FEATURES



**REINFORCEMENT**  
Multiple layers of high tensile synthetic cord



**COVER**  
Black colour of SBR blend compound. Abrasion and weather resistant



**INNER TUBE**  
Antistatic black SBR blend compound. High abrasion resistance.



**WORKING PRESSURE**  
Constant Pressure  
40 Bar / 580 PSI



**TEMPERATURE RANGE**  
-30°C to +80°C



**SAFETY FACTOR**  
3 : 1



### NOTE

Not suitable for corrosive chemicals or petroleum-based products. Always flush the hose after use to prevent material buildup and extend service life.



### SPECIFICATIONS

Part No.	ID		OD	Working Pressure		Burst Pressure		Length
	(inch)	(mm)	(mm)	(Bar)	(Psi)	(Bar)	(Psi)	(m)
ASH-PCH-025	1"	25.4	40	40	580	120	1740	30
ASH-PCH-032	1-1/4"	32	46	40	580	120	1740	30
ASH-PCH-038	1-1/2"	38	55	40	580	120	1740	30
ASH-PCH-051	2"	51	70	40	580	120	1740	30
ASH-PCH-063	2-1/2"	63.5	83.5	40	580	120	1740	30

Brand Reference: ASHFLEX PLASTER / CEMENT HOSE - ID 1" - W.P.40BAR/580PSI -