



Oil Discharge Hose 10 Bar



Application

Softwall hose used for transfer of oil and petroleum based products.

Tube: Black color of NBR blend compound. Oil resistance.

Cover: Black color of NBR blend compound. Oil, abrasion and weather resistance.

Reinforcement: Multiple layer of high tensile synthetic cord.

Temperature: -20°C to +90°C

Nominal inch	I.D (mm)	O.D (mm)	Pressure (bar)		Weight (Kg/m)	Length (m)
			Working	Burst		
3/4"	19.0	28.0	10	30	0.405	30
1"	25.4	35.0	10	30	0.568	30
1-1/4"	31.8	42.0	10	30	0.750	30
1-1/2"	38.1	48.0	10	30	0.843	30
2"	50.8	63.0	10	30	1.364	30
2-1/2"	63.5	75.5	10	30	1.367	30
3"	76.2	89.0	10	30	1.795	30
3-1/2"	88.9	102.0	10	30	2.050	30
4"	101.6	115.0	10	30	2.299	30
5"	127.0	141.0	10	30	2.639	30
6"	152.0	166.0	10	30	3.134	30
8"	203.2	219.0	10	30	4.059	12
10"	254.0	272.0	10	30	7.006	12
12"	304.0	323.0	10	30	9.141	12