



Oil Suction Hose 10 Bar



Application

Hardwall hose used for the suction of oil and petroleum based products.

Tube: Black color of NBR blend compound. Oil resistance.

Cover: Black color of NBR blend compound. Oil, abrasion and weather resistance.

Reinforcement: Multiple layers of high tensile synthetic cord and supported with helix wire.

Embedded with antistatic copper wire.

Temperature: -20°C to +90°C

Nominal inch	I.D (mm)	O.D (mm)	Pressure (bar)		Weight (Kg/m)	Length (m)
			Working	Burst		
1"	25.4	35.0	10	30	0.698	30
1-1/4"	31.8	43.0	10	30	1.012	30
1-1/2"	38.1	49.0	10	30	1.146	30
2"	50.8	63.0	10	30	1.763	30
2-1/2"	63.5	76.0	10	30	2.099	30
3"	76.2	89.0	10	30	2.579	30
3-1/2"	88.9	104.0	10	30	3.127	30
4"	101.6	117.0	10	30	3.947	30
5"	127.0	143.0	10	30	5.196	30
6"	152.0	170.0	10	30	6.638	30
8"	203.2	222.0	10	30	9.493	12
10"	254.0	277.0	10	30	13.972	12
12"	304.0	328.0	10	30	19.549	12