



# Water Discharge Hose 20 Bar



## Application

Softwall discharge hose used in water transfer, non-corrosive liquids, used in construction site, industries and agriculture.

Tube: Black color of NR blend compound.

Cover: Black color of NR blend compound. Abrasion and weather resistant.

Reinforcement: Multiple layer of high tensile synthetic cord.

Temperature: -20°C to +80°C

Nominal inch	I.D (mm)	O.D (mm)	Pressure (bar)		Weight (Kg/m)	Length (m)
			Working	Burst		
1/2"	12.7	21.0	20	60	0.277	30
3/4"	19.0	29.0	20	60	0.500	30
1"	25.4	35.0	20	60	0.566	30
1-1/4"	31.8	45.0	20	60	0.919	30
1-1/2"	38.1	51.0	20	60	1.033	30
2"	50.8	65.0	20	60	1.421	30
2-1/2"	63.5	78.0	20	60	1.680	30
3"	76.2	92.0	20	60	2.146	30
4"	101.6	118.0	20	60	2.982	30
5"	127.0	143.0	20	60	3.105	30
6"	152.0	170.0	20	60	3.700	30
8"	203.2	222.0	20	60	4.782	12
10"	254.0	278.0	20	60	7.086	12
12"	304.0	330.0	20	60	9.608	12