









Wiring Pins





Power Loss

protection

Sensing





Reliable & Stable Performance


Technical Data

Door sliding modes	Single-opening / Double-opening
Door leaf weight	≤1*150 kg / ≤2*140kg
Door leaf width	600-1200mm / 500-1150mm
Opening speed	150-500mm/s(Adjustable)
Closing speed	100-500mm/s(Adjustable)
Motor	24V 55W brushless DC motor
Opening time	0-9second(Adjustable)
Impact function	Rebounding up on impact
Voltage	AC220V 50Hz-60Hz
Operating Temperature	-20°C~60°C

Features & Advantages

- ♦ Microcomputer intelligent control and advanced mechanical configuration.
- ♦ Work at a range of power supply, low power consumption, energy-saving
- Intelligent control system, adjustable parameters
- ◆ Low noise drive unit, simple and convenient installation
- Advanced brushless motor and worm gear reducer integration, high efficiency, great torque, no powder pollution, quick in speed up and down, long service life.
- ♦ The unique self-locking function, need not extra accessories, full function remote control device, safe and reliable.
- ◆ Safety sensor, ensure safe passage
- ♦ Has a variety of trigger way to open the door
- ◆ In the event of a power failure, use the backup batteries to keep the door in normal operation.
- ◆ Self-locking function, when the door is fully closed, keep the state.

Sectional View



Accessories Optional

Handicap Toilet



















Wired Touchless Switch



Push Button



Handicap Toilet System-Wave Button

Battery Back-Up

SPL DOOR SOLUTIONS SDN BHD (1557918-A)