

EVO 250S MMA



Quick Specs

Light Duty Industrial Applications

Precision Metal Fabrication
Maintenance and Repair
Light Manufacturing
Tube and Pipe
Maintenance

Processes : MMA

Technical Data:

Power supply : 240V 1 Ph
Frequency : 50/60 (Hz)
Rated Input : 8.7 KVA
Rated Output Voltage : 28 V
Rated Output Current : 200 A
No Load Voltage : 74 V

Duty Cycle : 60%

Efficiency : 0.85

Power Factor : 0.76

Insulation Grade : F

Protection Grade : IP 23

Net Weight : 4.6 Kg

Dimensions : 280x160x240 mm
(LxWxH)



Features :-

Extra Function : Automatic arc force, hot start & anti-stick for greater control and ease of use.

Protections : Equipped with temperature, voltage and current sensor for high protection.

Generator friendly : Designed to work with diesel generators and to avoid failures due to its voltage spikes.

Weight : Extremely low weight and versatility.

Manufactured by :

WELDING INDUSTRIES (M) SDN BHD



Sole Distributor:

LONGLIFE WELD SDN BHD

kengfu@longlifeweld.com.my

sy.leong@longlifeweld.com.my

owt@longlifeweld.com.my

TOTAL WELDING SOLUTIONS