

**120F0231****Reciprocating compressor, NTZ068A4LR1B**

Refrigerants: R404A; R452A; R454C; R455A, Segment usage: Refrigeration LT,

Compressor power supply [V]: 400/3/50 460/3/60, Packing format: Industrial pack

PRODUCT DETAILS

Gross weight	24.83 Kilogram
Net weight	23.32 Kilogram
Volume	36.8 Liter
EAN	5702428521192
Type	NTZ068
Product group	Hermetic compressors
Product Name Description	Reciprocating compressor NTZ
Approval	CCC CE UL UKCA
Brand technique	Reciprocating compressor
Capacity control	Fixed speed
CE mark	Yes
China RoHS compliance	Yes with exemptions
China RoHS exemption clause	7.1 7.3
Colour	Blue
Compressor power supply [V]	400/3/50 460/3/60
Configuration code	Single
Connection type	Rotolock
Contains batteries	No
Cylinder	1
Description	NTZ068-4B
Diameter [mm]	224 mm
Discharge connection height [mm]	68 mm
Discharge connection pipe size [in]	1/2 in
Discharge connection size [in]	1 in
Drawing number	8501026f
Economizer	No
EU RoHS compliance	Yes with exemptions
EU RoHS exemption clause	6(a) 6(c)
Factory HP [bar]	25 bar
Factory LP [bar]	25 bar
Family	NTZ
Fitting remark	(shipped with rotolock version only)
Fitting sleeve	ODF
Fitting standard	Rotolock

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Product Detail | Reciprocating compressor, NTZ068A4LR1B

PRODUCT DETAILS

Frequency [Hz]	50/60
Gauge port HP	None
Gauge port LP	Schrader
Glass mounting	Threaded
Glass torque [Nm]	50 N-m
GP LP torque [Nm]	15 N-m
High Side TS Max	150 °C
High Side TS Min	-35 °C
High Side Volume	0.3 L
High value of nominal voltage at 50Hz [V]	400 V
High value of nominal voltage at 60Hz [V]	460 V
High value of voltage range at 50Hz [V]	440 V
High value of voltage range at 60Hz [V]	506 V
In scope of WEEE	No
IP protection class	IP55 (with cable gland)
Low Side TS Max	50 °C
Low Side TS Min	-35 °C
Low Side Volume	7.5 L
Low value of nominal voltage at 50Hz [V]	380 V
Low value of nominal voltage at 60Hz [V]	460 V
Low value of voltage range at 50Hz [V]	340 V
Low value of voltage range at 60Hz [V]	414 V
LRA	25 A
Max pressure (PS) - high side	28.5 bar
Max pressure (PS) - low side	22.6 bar
MCC	8.4 A
Model number	NTZ068A4LR1B
Motor protection	Internal overload protector
Mounting torque [Nm]	15 N-m
Network power supply [V/Ph/Hz]	380-415/3/50 460/3/60
Number of starts per hour [Max]	12
Oil charge [L]	0.95 L
Oil equalization	3/8" flare SAE
Oil equalization torque [Nm]	30 N-m
Oil reference	175PZ
Packing format	Industrial pack
Packing quantity	12
Phase	3
Power connections	Spade
REACH Candidate List substances	Lead (CAS no. 7439-92-1)
Refrigerant charge [kg] [Max]	2.5 kg
Refrigerants	R404A R452A R454C

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.



PRODUCT DETAILS

	R455A
Rotational speed at 50Hz [rpm]	2900 rpm
Rotational speed at 60Hz [rpm]	3500 rpm
SCIP dossier no.	5a332c1b-1d1b-4998-8115-d0929877ecb4
Segment usage	Refrigeration LT
Shipped fittings	Suction and discharge solder sleeves, rotolock nuts and gaskets
Suction connection height [mm]	263 mm
Suction connection material	-
Suction connection pipe size [in]	5/8 in
Suction connection size [in]	1 1/4 in
Swept volume [cm ³]	68 cm ³
Technology	Reciprocating
Test dif [bar] [Max]	30 bar
Test HP [bar] [Max]	30 bar
Test LP [bar] [Max]	25 bar
Torque earth [Nm]	3 N-m
Torque power [Nm]	3 N-m
Total height [mm]	333 mm
UL mark	Yes
Winding resistance for three-phase compressors with identical windings [Ohm]	6.67 Ohm

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)