

**120F0241****Reciprocating compressor, NTZ215A4LR1B**

Refrigerants: R404A; R452A, Segment usage: Refrigeration LT, Compressor power supply [V]: 400/3/50 460/3/60, Packing format: Industrial pack

**PRODUCT DETAILS**

|                                            |                                      |
|--------------------------------------------|--------------------------------------|
| <b>Gross weight</b>                        | 65.5 Kilogram                        |
| <b>Net weight</b>                          | 62 Kilogram                          |
| <b>Volume</b>                              | 104.267 Liter                        |
| <b>EAN</b>                                 | 5702428521116                        |
| <b>Type</b>                                | NTZ215                               |
| <b>Product group</b>                       | Hermetic compressors                 |
| <b>Product Name Description</b>            | Reciprocating compressor NTZ         |
| <b>Approval</b>                            | CE<br>UKCA                           |
| <b>Brand technique</b>                     | Reciprocating compressor             |
| <b>Capacity control</b>                    | Fixed speed                          |
| <b>CE mark</b>                             | Yes                                  |
| <b>China RoHS compliance</b>               | Yes with exemptions                  |
| <b>China RoHS exemption clause</b>         | 7.1<br>7.3                           |
| <b>Colour</b>                              | Blue                                 |
| <b>Compressor power supply [V]</b>         | 400/3/50 460/3/60                    |
| <b>Configuration code</b>                  | Single                               |
| <b>Connection type</b>                     | Rotolock                             |
| <b>Contains batteries</b>                  | No                                   |
| <b>Cylinder</b>                            | 4                                    |
| <b>Description</b>                         | NTZ215-4B                            |
| <b>Diameter [mm]</b>                       | 352 mm                               |
| <b>Discharge connection height [mm]</b>    | 125 mm                               |
| <b>Discharge connection pipe size [in]</b> | 3/4 in                               |
| <b>Discharge connection size [in]</b>      | 1 1/4 in                             |
| <b>Drawing number</b>                      | 8504010f                             |
| <b>Economizer</b>                          | No                                   |
| <b>EU RoHS compliance</b>                  | Yes with exemptions                  |
| <b>EU RoHS exemption clause</b>            | 6(a)<br>6(c)                         |
| <b>Factory HP [bar]</b>                    | 25 bar                               |
| <b>Factory LP [bar]</b>                    | 25 bar                               |
| <b>Family</b>                              | NTZ                                  |
| <b>Fitting remark</b>                      | (shipped with rotolock version only) |
| <b>Fitting sleeve</b>                      | ODF                                  |
| <b>Fitting standard</b>                    | Rotolock                             |
| <b>Frequency [Hz]</b>                      | 50/60                                |
| <b>Gauge port HP</b>                       | None                                 |

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

## Product Detail | Reciprocating compressor, NTZ215A4LR1B

## PRODUCT DETAILS

|                                           |                                      |
|-------------------------------------------|--------------------------------------|
| Gauge port LP                             | Schrader                             |
| Glass mounting                            | Threaded                             |
| Glass torque [Nm]                         | 50 N-m                               |
| GP LP torque [Nm]                         | 15 N-m                               |
| High Side TS Max                          | 150 °C                               |
| High Side TS Min                          | -35 °C                               |
| High Side Volume                          | 1.2 L                                |
| High value of nominal voltage at 50Hz [V] | 400 V                                |
| High value of nominal voltage at 60Hz [V] | 460 V                                |
| High value of voltage range at 50Hz [V]   | 460 V                                |
| High value of voltage range at 60Hz [V]   | 506 V                                |
| In scope of WEEE                          | No                                   |
| IP protection class                       | IP54 (with cable gland)              |
| Low Side TS Max                           | 50 °C                                |
| Low Side TS Min                           | -35 °C                               |
| Low Side Volume                           | 31 L                                 |
| Low value of nominal voltage at 50Hz [V]  | 380 V                                |
| Low value of nominal voltage at 60Hz [V]  | 460 V                                |
| Low value of voltage range at 50Hz [V]    | 340 V                                |
| Low value of voltage range at 60Hz [V]    | 414 V                                |
| LRA                                       | 74 A                                 |
| Max pressure (PS) - high side             | 28.5 bar                             |
| Max pressure (PS) - low side              | 22.6 bar                             |
| MCC                                       | 22.3 A                               |
| Model number                              | NTZ215A4LR1B                         |
| Motor protection                          | Internal overload protector          |
| Mounting torque [Nm]                      | 15 N-m                               |
| Network power supply [V/Ph/Hz]            | 380-415/3/50 460/3/60                |
| Number of starts per hour [Max]           | 12                                   |
| Oil charge [L]                            | 3.9 L                                |
| Oil equalization                          | 3/8" flare SAE                       |
| Oil equalization torque [Nm]              | 30 N-m                               |
| Oil reference                             | 175PZ                                |
| Packing format                            | Industrial pack                      |
| Packing quantity                          | 6                                    |
| Phase                                     | 3                                    |
| Power connections                         | Screw connectors 10-32 UNF x 9.5     |
| REACH Candidate List substances           | Lead (CAS no. 7439-92-1)             |
| Refrigerant charge [kg] [Max]             | 10 kg                                |
| Refrigerants                              | R404A<br>R452A                       |
| Rotational speed at 50Hz [rpm]            | 2900 rpm                             |
| Rotational speed at 60Hz [rpm]            | 3500 rpm                             |
| SCIP dossier no.                          | 6971587b-85b6-4808-886d-274e8a9998d4 |

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.



## PRODUCT DETAILS

|                                                                                     |                                                                    |
|-------------------------------------------------------------------------------------|--------------------------------------------------------------------|
| Segment usage                                                                       | Refrigeration LT                                                   |
| Shipped fittings                                                                    | Suction and discharge solder sleeves,<br>rotolock nuts and gaskets |
| Suction connection height [mm]                                                      | 233 mm                                                             |
| Suction connection material                                                         | -                                                                  |
| Suction connection pipe size [in]                                                   | 1 1/8 in                                                           |
| Suction connection size [in]                                                        | 1 3/4 in                                                           |
| Swept volume [cm <sup>3</sup> ]                                                     | 215 cm <sup>3</sup>                                                |
| Technology                                                                          | Reciprocating                                                      |
| Test dif [bar] [Max]                                                                | 30 bar                                                             |
| Test HP [bar] [Max]                                                                 | 30 bar                                                             |
| Test LP [bar] [Max]                                                                 | 25 bar                                                             |
| Torque earth [Nm]                                                                   | 3 N-m                                                              |
| Torque power [Nm]                                                                   | 3 N-m                                                              |
| Total height [mm]                                                                   | 519 mm                                                             |
| Winding resistance for three-<br>phase compressors with identical<br>windings [Ohm] | 2.23 Ohm                                                           |

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)