

# Product sheet



## ELOE LEGRAND

### Eloe - 4 gang 1way switch - White

REF. 618006 | EAN. 3414972265478

> [Visit e-catalogue](#)

## Product characteristics

- 16AX, 250V
- ELOE is sold as a complete set under one cat number
- Screw type terminals for enhanced contacts
- Marked terminals for easy identification
- Glossy white finish

## Recommendation / Restriction

- Recommended inside use only

## The product's benefits

### Installation

- Quick and Easy rocker plate clipping system

### Usage

- Practical 4-points lighting control on a single device

### Advantages

- Optimised range for new builds & renovation projects
- Delivered with screws for flush & surface boxes in both plastic and metal boxes
- A squarish shape designed with a full rocker plate aesthetic

## Technical characteristics

|                      |                                     |
|----------------------|-------------------------------------|
| Wiring system        | Switch 1-pole                       |
| Method of operation  | Rocker lever                        |
| Assembly arrangement | Basic element with full cover plate |
| Push button switch   | No                                  |
| Number of rockers    | 4                                   |
| Mounting method      | Flush-mounted                       |
| Type of fastening    | Screw mounting                      |

|                                         |                  |
|-----------------------------------------|------------------|
| Monitoring contact                      | No               |
| Connection type                         | Screwed terminal |
| Heating switch                          | No               |
| Device width                            | 86 mm            |
| Device height                           | 86 mm            |
| Device depth                            | 35.9 mm          |
| Built-in depth                          | 19.5 mm          |
| Min. depth of built-in installation box | 35 mm            |

|                                         |               |
|-----------------------------------------|---------------|
| With mounting plate                     | No            |
| Material                                | Plastic       |
| Material quality                        | Thermoplastic |
| Halogen free                            | Yes           |
| Antimicrobial treatment                 | No            |
| Surface protection                      | Untreated     |
| Surface finishing                       | Glossy        |
| Colour                                  | White         |
| RAL-number (similar)                    | 9003          |
| Colour of switch operator               | White         |
| Suitable for degree of protection (IP)  | IP20          |
| degree of impact strength (IK)          | IK04          |
| Nominal voltage                         | 250 V         |
| Rated current                           | 16 A          |
| Switching current for fluorescent lamps | 16 AX         |

|                                  |                     |
|----------------------------------|---------------------|
| Compatible with Apple HomeKit    | No                  |
| Compatible with Google Assistant | No                  |
| Compatible with Amazon Alexa     | No                  |
| IFTTT support available          | No                  |
| Operating / setting temperature  | -5-50 °C            |
| Storage temperature              | -10-70 °C           |
| Voltage type                     | AC                  |
| Frequency                        | 50-60 Hz            |
| Mandatory neutral                | No                  |
| Terminal marking indication      | Yes                 |
| Terminals capacity               | 1-4 mm <sup>2</sup> |
| Cable nature for connection      | Flexible or rigid   |
| Cable section                    | 1-4 mm <sup>2</sup> |

## Documentation

### TECHNICAL DOCUMENTATION

 F03721EN-00.pdf | PDF (0.7Mo)

 LE13420AA.pdf | PDF (0.99Mo)

### Agreements & Certificates

 OC / CB-CN56381-M2 | (0.21Mo)

 OC / CB-CN56381-M3 | (0.51Mo)

 LGRP-01476-V01.01-EN.pdf | PDF (0.61Mo)

### CATALOGUE PAGE & OTHERS

 ex223001\_0661.pdf | PDF (0.07Mo)