

Product sheet



ELOE LEGRAND

Eloe - 1 gang British Standard 13A single pole switched socket - White

REF. 618041 | EAN. 3414972264846

> [Visit e-catalogue](#)

Product characteristics

- 2P+E British Standard, 13A, 250V
- ELOE is sold as a complete set under one cat number
- Screw type terminals for a secured & enhanced contacts
- Marked terminals for easy identification
- Glossy white finish

Recommendation / Restriction

- Recommended inside use only

The product's benefits

Installation

- Quick and Easy plate clipping system

Usage

- Fitted with safety shutters to maximise child protection

Advantages

- Delivered with its protective shell against paint and dust during installation phase
- Delivered with screws for flush & surface boxes in both plastic and metal boxes
- A squarish shape designed with a full rocker plate aesthetic

Technical characteristics

Model	British Standard
Concurrently switching neutral conductor	No
Protective contact	Flat
Number of active contacts (round)	0
Number of active contacts (flat)	2
Number of active contacts (square)	0
Assembly arrangement	Basic element with full cover plate

Material quality	Thermoplastic
Halogen free	Yes
Surface protection	Untreated
Surface finishing	Glossy
Antimicrobial treatment	No
With on/off switch	Yes
Nominal current	13 A

With complementary luminous signal	No
Number of ports USB-A	0
Number of ports USB-C	0
Number of socket outlets	1
Socket outlets phase-separated	No
Number of modules (module system)	2
Number of socket outlets switchable	1
Number of phases	1
Connection type	Screwed terminal
With hinged lid	No
With enhanced contact protection	Yes
Colour	White
RAL-number (similar)	9003
Metallic colour	No
Transparent	No
Eject-mechanism	No
With function lighting	No
With orientation lighting	No
Overvoltage protection	No
Fault current protection	No
With miniature fuse	No
Special power supply	None
Mounting method	Flush-mounted
Type of fastening	Mounting with screw
Material	Plastic

Nominal voltage	250 V
Frequency	50-60 Hz
Suitable for degree of protection (IP)	IP20
degree of impact strength (IK)	IK04
Device width	86 mm
Device height	86 mm
Device depth	35 mm
Min. depth of built-in installation box	35 mm
Compatible with Apple HomeKit	No
Compatible with Amazon Alexa	No
Compatible with Google Assistant	No
IFTTT support available	No
With Wi-Fi signal repeater	No
With built-in bluetooth speaker	No
For heavy conditions according to VDE	No
Built-in depth	22.7 mm
Operating / setting temperature	-5-50 °C
Storage temperature	-10-70 °C
Voltage type	AC
Terminal marking indication	Yes
Prewired	No
Terminals capacity	1-4 mm ²
Cable nature for connection	Flexible or rigid
Cable section	1-4 mm ²
Connected object	No

Documentation

TECHNICAL DOCUMENTATION

 F03727EN-00 .pdf | PDF (0.6Mo)

Agreements & Certificates

 LGRP-01478-V01.01-EN.pdf | PDF (0.57Mo)

 G-MARK-0048-1539 | (0.58Mo)

 OC / CB-FR_714774 | (0.33Mo)

 OC / CB-FR_719315 | (0.61Mo)

CATALOGUE PAGE & OTHERS

 ex223001_0665.pdf | PDF (0.09Mo)



AoC-N°2566AS03ARLI58973 | (0.32Mo)