

Product sheet



ELOE LEGRAND

Eloe - 1 gang multistandard single pole switched socket - White

REF. 618067 | EAN. 3414972265218

> [Visit e-catalogue](#)

Product characteristics

- 2P+E Multi standard, 250V
- ELOE is sold as a complete set under one cat number
- Screw type terminals for a secured & enhanced contacts
- Marked terminals for easy identification
- Glossy white finish

Recommendation / Restriction

- Recommended inside use only

The product's benefits

Installation

- Quick and Easy plate clipping system

Usage

- Fitted with safety shutters to maximise child protection

Advantages

- Delivered with its protective shell against paint and dust during installation phase
- Delivered with screws for flush & surface boxes in both plastic and metal boxes
- A squarish shape designed with a full rocker plate aesthetic

Technical characteristics

Model	Multi-standard socket
Protective contact	Other
Number of active contacts (round)	2
Number of active contacts (flat)	2
Assembly arrangement	Basic element with full cover plate
With complementary luminous signal	No
Number of ports USB-A	0

Surface protection	Untreated
Surface finishing	Glossy
Antimicrobial treatment	No
With on/off switch	Yes
Nominal current	16 A
Nominal voltage	250 V
Frequency	50-60 Hz

Number of ports USB-C	0
Number of socket outlets switchable	1
Number of phases	1
Connection type	Screwed terminal
With hinged lid	No
With enhanced contact protection	Yes
Colour	White
RAL-number (similar)	9003
Metallic colour	No
Transparent	No
Eject-mechanism	Yes
With function lighting	No
With orientation lighting	No
Overvoltage protection	No
Fault current protection	No
With miniature fuse	No
Special power supply	None
Mounting method	Flush-mounted
Type of fastening	Mounting with screw
Material	Plastic
Material quality	Thermoplastic
Halogen free	Yes

Suitable for degree of protection (IP)	IP20
degree of impact strength (IK)	IK04
Device width	86 mm
Device height	86 mm
Min. depth of built-in installation box	35 mm
Compatible with Apple HomeKit	No
Compatible with Amazon Alexa	No
Compatible with Google Assistant	No
IFTTT support available	No
With Wi-Fi signal repeater	No
With built-in bluetooth speaker	No
For heavy conditions according to VDE	No
Built-in depth	20.9 mm
Operating / setting temperature	-5-50 °C
Storage temperature	-10-70 °C
Voltage type	AC
Terminal marking indication	Yes
Prewired	No
Terminals capacity	1-4 mm²
Cable nature for connection	Flexible or rigid
Cable section	1-4 mm²
Connected object	No

Documentation

TECHNICAL DOCUMENTATION

 [F03741EN-00.pdf](#) | PDF (0.52Mo)

Agreements & Certificates

 [LGRP-01479-V01.01-EN.pdf](#) | PDF (0.61Mo)

CATALOGUE PAGE & OTHERS

 [ex223001_0666.pdf](#) | PDF (0.07Mo)