

Product sheet



ELOE LEGRAND

Eloe - 1 gang 20A double pole switch + neon + one earth - White

REF. 618071 | EAN. 3414972264082

> [Visit e-catalogue](#)

Product characteristics

- 20AX, 250V
- ELOE is sold as a complete set under one cat number
- Screw type terminals for enhanced contacts
- Marked terminals for easy identification
- Glossy white finish

Recommendation / Restriction

- Recommended inside use only

The product's benefits

Installation

- Quick and Easy plate-rocker clipping system

Usage

- Complies with British Standards certifications for heavy loads

Advantages

- Optimised range for new builds & renovation projects
- Delivered with screws for flush & surface boxes in both plastic and metal boxes
- A squarish shape designed with a full rocker plate aesthetic

Technical characteristics

Wiring system	Switch 2-pole
Method of operation	Rocker lever
Assembly arrangement	Basic element with full cover plate
Push button switch	No
Number of rockers	1
Mounting method	Flush-mounted
Type of fastening	Screw mounting

Rated current	20 A
Switching current for fluorescent lamps	20 AX
Monitoring contact	No
Connection type	Screwed terminal
Heating switch	No
Device width	86 mm
Device height	86 mm

With mounting plate	No
Material	Plastic
Material quality	Thermoplastic
Halogen free	Yes
Antimicrobial treatment	No
Surface protection	Untreated
Surface finishing	Glossy
Colour	White
RAL-number (similar)	9003
Colour of switch operator	White
Lighting	Yes
Function lighting	Illuminated (on)
Type of lighting	LED exchangeable
Suitable for degree of protection (IP)	IP20
degree of impact strength (IK)	IK04
Nominal voltage	250 V

Device depth	36.8 mm
Built-in depth	20.5 mm
Min. depth of built-in installation box	35 mm
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No
Operating / setting temperature	-5-50 °C
Storage temperature	-10-70 °C
Voltage type	AC
Frequency	50-60 Hz
Mandatory neutral	Yes
Terminal marking indication	Yes
Terminals capacity	1-4 mm ²
Cable nature for connection	Flexible or rigid
Cable section	1-4 mm ²

Documentation

TECHNICAL DOCUMENTATION

 F03722EN-00.pdf | PDF (0.5Mo)

 LE13420AA.pdf | PDF (0.99Mo)

Agreements & Certificates

 OC / CB-CN56379-M2 | (0.56Mo)

 OC / CB-CN56379 | (0.34Mo)

CATALOGUE PAGE & OTHERS

 ex223001_0662.pdf | PDF (0.07Mo)