



Professional Wireless CONFERENCE SYSTEM

CSD-802
(Delegate Unit)

CSC-801
(Chairman Unit)

CSA-800
(Center Amp)

*Reliable Performance for **Modern Meeting Rooms***



Professional Wireless Conference System

CSA-800

- Intelligent Battery Management System
- Encrypted Secure Communication
- Stable Multi Channel Architecture
- Adaptive Frequency Hopping
- Zero Setup Auto Pairing



Channel Setting Button

Volume Knob

Power Switch

Menu Function Knob



Meeting Microphone TRANSMITTER

The wireless gooseneck microphone features a flexible neck for precise positioning, ensuring clear, professional-grade audio for every speaker in any meeting setting.



Chairman microphone have
speech priority function.
Delegates microphone
only have speech
function.

CSC-801
(Chairman Unit)

CSD-802
(Delegate Unit)



Receiver Menu

INSTRUCTIONS



By default twist for ADJ volume, long press ADJ lock operation.

CH - A.B.C.D key: short press the hand-held or pockets transmitters can be infrared frequency, long press for frequency adjustment.

The ESC/Close TX: click the exit menu operation, long press a button to turn it off (shut down all the launch).

The power switch

The meeting mode

First in first out: first into a state representative launch will be apply on behalf of the out. (portable, pockets, permissions for the President) Rob wheat: first into a state of the receiver, to manually to exit the speech the chairman or a key mute, behind the application state of representatives spoke to enter.

Chairman preferred: chairman, on behalf of automatically into the mute state. (this feature is to pay attention to when using, chairman of the meeting with speaker placement)

ID: if more than two sets of systems use, can be set on the transmitter tracking mode, set the specified ID can not affect the use.

Languages: Chinese, English menu display Settings.

WIFI: can manual modulation WIFI channel, the host in the boot automatically scan to use clean channel, if there is a wi-fi interference in use process, will ensure that speech condition of the unit is not affected, automatic scanning to clean channel.

Reset: restore factory Settings.



Transmitter Menu

INSTRUCTIONS



WIFI single indicator

AUTO: Automatic mode, it can be use with any receiver.

TRACK: Tracking mode, in this mode, the unit only with the corresponding ID host to use, suitable for multiple systems.

CHM: It's set to be Chairman.

REP: It's set to be Delegate

Set the trace or automatic mode: in boot mode, long press power don't let go 8 seconds, and then through the power button Settings, in tracking mode can search working host ID.

Set up a Chairman or Delegate: In the boot state, long press power and mute buttons 8 seconds, enter the set state.

Technical Parameters

Specifications

Receiver Parameters

Transmitter Parameters

Usage Frequency

630 - 690MHz

630 - 690MHz

Wi-Fi Frequency

410 - 480MHz

410 - 480MHz

Operating Voltage

DC12 - 15V

DC3V

Working Current

750mA

110mA



Professional Wireless Conference Microphone System in Action



Features & Operation

The installation is simple, easily many people in the meeting room studio basic don't need to debug, quickly to complete the installation.

The function operation is extremely simple, the function of the one click into operation at a glance.

The frequency automatic tracking locking function without the frequency, out of the box conference unit.

Built in channel 16 WIFI, WIFI frequency hopping technology, detect disturbance, frequency jump automatically, is to speak the units are not affected.

Built in 520 speech channel, to avoid interference.

Built in advanced encryption communication algorithm, completely eliminate communication errors and false action.

Built in battery monitoring functions. Meeting real time display battery power.

Built in priority, chairman of the speech, grab, fifo functionality.

Wireless capabilities, hand in hand to support an infinite number of units used, spokesman for four at the same time.

Meeting with automatic shutdown function. Host without electricity for more than half an hour, the meeting unit will automatically shut down.

Meeting unit can choose tracking mode and automatic mode, use tracking mode, you can specify a tracking receiver.

The operating menu can choose Chinese or English.

The host can be a button to turn off all the launch host, convenient operation.

Handheld microphones and meeting unit can be used mixed.