

ASHFLEX WATER DISCHARGE HOSE 10 BAR

Common Application

The Water Discharge Hose is designed for the delivery of water and non-corrosive liquids in a wide range of industrial, agricultural, construction, and municipal applications.

Typical Applications

- Discharging water from pumps at construction sites, quarries, and mines
- Agricultural irrigation and water distribution systems
- Dewatering ponds, trenches, and flooded areas
- Washdown operations in factories and shipyards
- Municipal water transfer and drainage projects



Key Features

Reinforcement: Multi - layers of high tensile textile cords

Cover: Black colour of NR blend compound

Inner Tube: Black colour of NR blend compound

Working Pressure: Constant Pressure 10 Bar / 150PSI

Temperature Range: -20°C to +80°C

Safety Factor: 3 : 1

Note

Not suitable for suction applications. For combined suction and discharge operations, use a Water Suction & Discharge Hose. Always confirm compatibility with the liquid being transferred.

Part No.	ID		OD (mm)	Working Pressure		Burst Pressure		Length (m)
	(inch)	(mm)		(Bar)	(Psi)	(Bar)	(Psi)	
ASH-WDH-1006	1/4"	6.4	13	10	150	30	450	100
ASH-WDH-1007	5/16"	7.9	15	10	150	30	450	100
ASH-WDH-1009	3/8"	9.5	16	10	150	30	450	100
ASH-WDH-1012	1/2"	12.7	22	10	150	30	450	100
ASH-WDH-1019	3/4"	19.1	29	10	150	30	450	100
ASH-WDH-1025	1"	25.4	35	10	150	30	450	100
ASH-WDH-1031	1-1/4"	31.8	42	10	150	30	450	60
ASH-WDH-1038	1-1/2"	38.1	48	10	150	30	450	60
ASH-WDH-1050	2"	50.8	62	10	150	30	450	60
ASH-WDH-1063	2-1/2"	63.5	76	10	150	30	450	60
ASH-WDH-1076	3"	76.2	89	10	150	30	450	60
ASH-WDH-1102	4"	101.6	116	10	150	30	450	60
ASH-WDH-1127	5"	127	142	10	150	30	450	60
ASH-WDH-1152	6"	152	167	10	150	30	450	60
ASH-WDH-1203	8"	203	219	10	150	30	450	40
ASH-WDH-1254	10"	254	274	10	150	30	450	12
ASH-WDH-1305	12"	305	322	10	150	30	450	12

Brand Reference :ASHFLEX WATER DISCHARGE HOSE - ID 1/4" - W.P.10BAR/150PSI -