



PERFECT FILM SDN.BHD. (1057030-V)

Supply & Install Solar Control Window Film, Security Film For Auto & Building,
Sandblast Film, Patterned Design Film & Colour Sticker Etc.
10, Jalan BPU 6, Bandar Puchong Utama, 47100 Puchong Selangor Darul Ehsan, Malaysia
Tel: +603-5882 9849 Fax: +603-5882 9847 Email: perfect_film@yahoo.com.my

9G & 9M Series

CUT VINYL

DATA SHEET

Description

High performance calendered film in luxurious glossy and matte colors, user-friendly with excellent dimensional stability and weeding characteristic.

| | |
|------------------|------------------------------|
| Face film | Monomeric PVC made in Taiwan |
| Thickness | 85 μ m (3.4mil) \pm 5% |
| Color and Finish | glossy colors & matte colors |

Release liner

Premium quality Single-PE coated silicone paper imported from Japan.

| | |
|-----------|----------------------|
| Weight | 120 gsm \pm 5% |
| Thickness | 150 μ m \pm 5% |
| Finish | White with MY WINDOW |

Adhesive

Clear, permanent, solvent-based adhesive, non-residue, made in Taiwan.

| | |
|--------------------|---------------------------------------|
| Type | Acrylic |
| Apply Temp. | +10°C ~ +40°C |
| Adhesion (20 min) | 800~1,400 g/25mm |
| Adhesion (24 hour) | 1,000~1600 g/25mm |
| Cohesion | 24 hours \uparrow with 1 kg loading |

Application

Designed for use on cutting plotter system, for decoration, indoor and outdoor general signage, automotive and window graphics. Suitable for slightly curved application.

Storage

Shelf life is 1 years in original packaging, at 25°C and 50% relative humidity.

Length and Width

| | |
|--------|---|
| Length | 50 meters |
| Width | 0.92m (36") / 1.220m (48") / 1.524m (60") / |