

GOODY WEATHER TOP

Product Name	GOODY WEATHER TOP
Product Description	GOODY Weather Top is an exterior wall emulsion. Specially formulated to withstand tropical climate, GOODY Weather Top is formulated to last longer than ordinary emulsion paint.
Designed Use	For use on new or previously painted exterior masonry surfaces such as brickwork, plaster and cement rendering where a tough exterior coating is required.
Binder Type	Acrylic binder
Performance	<ul style="list-style-type: none"> • 5 Years' Protection • Good fungal and algae growth resistance • Good colour retention • Tough synthetic finish – washable • Good weathering property • No added lead or mercury • Low VOC and odour • Approved by SIRIM to Malaysian Standard MS 134:2007
Physical Properties Coverage* Volume Solids Dry Film Thickness Wet Film Thickness	10 – 12 m ² /Lt @ 25 microns 38% 25 microns / coat 63 microns / coat
Finishing Colours Finishing Pack Size	Refer to Kansai Paint's colour card Matt 1, 5 & 15 litres
Application Drying Times Dilution Cleaning Up	Surface dry : 20 mins ; Recoat : 1-2 hours (Dependent on temperature and humidity) Clean household water Clean household water
Dilution Ratio Brush or Roller Conventional Spray Airless Spray	Ready for use. If dilution is required, add up to 5% clean water. Dilution up to 10% water. Ready for use.
Spray Equipment Guide Conventional Spray Airless Spray	A typical set up would be a minimum atomising pressure of 2.8 kg/cm ² and fluid pressure of 0.4 kg/cm ³ with a nozzle size of 0.43 mm. A typical set up would be a minimum of 155 kg/cm ³ with nozzle size of 0.38 - 0.43 mm and a spray tip angle of 65°.
Surface Preparation	New, unpainted surfaces Allow surfaces to cure and dry out at least 28 days. Large cracks must be repaired with cement: sand mix and rendered smooth. Make good all minor defects with appropriate exterior grade fillers. Remove all loosely adhering residues by thorough brushing.

	<p>Repainting Check for fungus and algae growth. If present, treat the surfaces with fungicidal wash by brushing onto the surface with bleach mix (1 part household bleach with 3 parts water). Allow the mixture to penetrate the affected surface. Make good all defects with inappropriate patching materials. Once dry, remove all fungi, algae, chalk, loosely adhering contaminants by using high-pressure water jetting. Check for powder - if present, the surface must be sealed with a coat of PAR Plasterseal solvent base wall sealer.</p>																
<p>Recommended Paint System</p>	<p>New, unpainted surfaces :</p> <table border="1"> <thead> <tr> <th colspan="2">1st</th> <th colspan="2">2nd & 3rd</th> </tr> </thead> <tbody> <tr> <td>GOODY AR Wall Sealer</td> <td>Recoat 1 - 2 hours</td> <td>GOODY Weather Top</td> <td>Recoat 1 - 2 hours</td> </tr> </tbody> </table> <p>Repainting :</p> <table border="1"> <thead> <tr> <th colspan="2">1st</th> <th colspan="2">2nd & 3rd</th> </tr> </thead> <tbody> <tr> <td>PAR Plasterseal</td> <td>Recoat 4 - 5 hours</td> <td>GOODY Weather Top</td> <td>Recoat 1 - 2 hours</td> </tr> </tbody> </table> <p>NB : GOODY AR Wall Sealer and PAR Plasterseal work best on surfaces with a moisture content of below 15% and alkalinity below pH-9, otherwise premature paint failure may occur.</p>	1st		2nd & 3rd		GOODY AR Wall Sealer	Recoat 1 - 2 hours	GOODY Weather Top	Recoat 1 - 2 hours	1st		2nd & 3rd		PAR Plasterseal	Recoat 4 - 5 hours	GOODY Weather Top	Recoat 1 - 2 hours
1st		2nd & 3rd															
GOODY AR Wall Sealer	Recoat 1 - 2 hours	GOODY Weather Top	Recoat 1 - 2 hours														
1st		2nd & 3rd															
PAR Plasterseal	Recoat 4 - 5 hours	GOODY Weather Top	Recoat 1 - 2 hours														
<p>Safety & Health Information</p>	<ul style="list-style-type: none"> • Ensure adequate lighting and ventilation during application and drying. • This product does not contain added lead or mercury. • When applying paints, it is advisable to wear eye protection. • In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. • Use soap and water to remove splashes from skin. • Storage: Keep container closed and store in clean and dry conditions. • Dispose of contents and container in accordance with all local, regional, national and international regulations. • Do not empty into drains or water courses. • This product is not flammable. Keep out of reach of children. • Safety Data Sheet (SDS) is available upon request. 																

For further information on Product Data, please contact :

Decorative Sales Department

Kansai Paint Asia Pacific Sdn. Bhd. (705919-W)
4, Solok Waja 2, Kawasan Perindustrian Bukit Raja, 41710, Klang, Selangor, Malaysia.
Website : www.kansaimalaysia.com Tel : +60 3 3362 2388 Fax : +60 3 3342 7223

**Practical coverage will vary according to the roughness and porosity of surface to be painted, the application method and condition, dry film and thickness and the skill of applicator.*

The information in this technical data sheet is given to the best of our knowledge based on laboratory testing and practical experience and is provided as a general advice only. No guarantee of results is implied since the conditions of use are beyond our control. It is the responsibility of the users to ensure the suitability and proper usage of the product. We reserve the right to change the data without prior notice.