



PROCESS
DRILLING

SCY-38WSPM PERMANENT MAGNETIC DRILL

TECHNICAL SHEET



Technical Parameter		
Product model		SCY – 38WSPM
Core drill diameter	(mm)	Ø38
Rated voltage	(V)	220
Rated frequency	(Hz)	50
Rated input power	(W)	1650
No-load speed	(rpm)	570
Max attraction	(N)	14500
Cutting Depth	(mm)	35
Stroke	(mm)	45
Packing size	(mm)	350x250x430
Net/Gross weight	(kg)	11.5/18

FEATURES

- Magswitch permanent magnet generates magnetic force without requiring electrical input
- Suitable for small workplace
- Small size and easy carrying
- Strong drilling capacity and high efficiency
- Strong adhesion and reliable safety



STANDARD ACCESSORIES

- DRILL MACHINE
- WRENCH
- MANUAL
- SAFETY CHAIN
- HANDLE
- ALLEN WRENCH
- COOLANT BOTTLE
- TOOL BOX

SCY-35PM PERMANENT MAGNETIC DRILL

TECHNICAL SHEET

Technical Parameter		
Product model		SCY – 35PM
Core drill diameter	(mm)	Ø35
Twist drill diameter	(mm)	Ø13
Rated voltage	(V)	220
Rated frequency	(Hz)	50
Rated input power	(W)	1600
No-load speed	(rpm)	810
Max attraction	(N)	16000
Cutting Depth	(mm)	35
Stroke	(mm)	210
Packing size	(mm)	340x250x430
Net/Gross weight	(kg)	11.5/18

FEATURES

- Magswitch permanent magnet generates magnetic force without requiring electrical input
- Lightweight, high efficiency, small size.
- Operation is safe and convenient
- Strong suction magnetic seat
- Cooling and lubricating integrated device



STANDARD ACCESSORIES

- DRILL MACHINE
- WRENCH
- MANUAL
- SAFETY CHAIN
- HANDLE
- ALLEN WRENCH
- COOLANT BOTTLE
- TOOL BOX