

GROW[®] wall mount series



FRONT TEMPERED GLASS DOOR OR FULLY PERFORATED DOOR

FEATURES :

- Variety of heights
- Reliable welded main frame
- Vented top and bottom
- Comply with 19" wall mount standard
- Front lockable door with either Perspex with frame or Perforated
- Suitable for stand alone or wall mount installation
- Feet and castors can be provided for standing installation
- Adjustable mounting rails front and back
- Colour - Fully epoxy powder coated

STANDARD ORDER COMPRISES OF :

- Main frame
- Front door - Perforated with cam lock
- 2pcs Side panels
- Panel mount support - 2pcs for 6U/ 9U, 4pcs for 12U/ 15U
- 1pc 3 Gang trailing socket
- 1 Pack of M6 caged nuts & screws (20pcs)
- Earthing screw

Model	Capacity (U)	Height (mm)	Width (mm)	Depth (mm)	Packing Dimension (H*W*D)	Volume (CBM)
P/G0440WM	4	277	600	400	255 x 615 x 415	0.0648
P/G0650WM	6	355	600	500	353 x 610 x 540	0.1163
P/G0950WM	9	467	600	500	486 x 610 x 540	0.1601
P/G1250WM	12	595	600	500	619 x 610 x 540	0.2039
P/G1550WM	15	730	600	500	753 x 610 x 540	0.2480

* P = Perforated door, G = Glass door

* Customized sizes available upon request



GV INDUSTRIES SDN. BHD.