



CS620 / CS840

6" / 8" 20 / 40W 100V Line



CS518

5" 20W 100V Line

**CS620 / 840 : CO-AXIAL CEILING SPEAKER**

CS620 and 840 meets the requirement of hi fidelity of sound reproduction in areas such as function halls, restaurants and also for sound reinforcement at banquet halls. They are available in 6" and 8" version of speaker driver with tweeter and 100V line matching transformer.

**Packing information**

CS620 : 740(W) x 545 (H) x 275 (D) mm  
: 22.7 kg  
: 8 uts per carton

CS840 : 740 (W) x 630 (H) x 340 (D) mm  
: 21 kg  
: 8 uts per carton

**CS518 : SQUARE CO-AXIAL CEILING SPEAKER**

CS518 matches other fittings at ceiling where most of them are in square or rectangular shapes. It's size is almost similar to square shape light fittings and is loaded with co-axial 5" driver, delivering clear and crispy sound. It is suitable for boutiques, residence, offices as well as lobbies.

**Packing information**

CS518 : 580(W) x 510 (H) x 310 (D) mm  
: 17.1 kg  
: 7 uts per carton

**Technical Specifications**

	CS620	CS840	CS518
<b>SPEAKER</b>			
Power rating	20W 100V	40W 100V	20W 100V
Diameter	6.5" (165 mm)	8" (200 mm)	5" (125 mm)
Cone type	Co-axial		
Impedance	8 Ohm		
Freq response @ 1KHz +/- 3dB	80 ~ 18 KHz	90 ~ 19 KHz	100 ~ 18 KHz
SPL @ 1W / m (+/- 3dB) 1 KHz	88 dB	90 dB	85 dB
	10 oz	15 oz	10 oz
<b>TRANSFORMER</b>			
Tapping (100V line)	20W	40W	2.5 / 5 / 10 / 20W
Primary impedance (Ohm)	500	250	4K / 2K / 1K / 500
Secondary impedance (Ohm)	8		
<b>PHYSICAL</b>			
Grille / enclosure	White metal / ABS white		
Cutting hole dim	205 mm	240 mm	150 x 150 mm
Overall size (dia x height)	240 x 145 mm	280 x 145 mm	180 x 180 x 135 mm
Weight	2.4 kg	2.1 kg	1.8 kg
Colour	White		