

S125 series

Ø125mm LED Steady/ Flashing Signal Lights



S125L



Feature of indirect light diffusing system

Qlight's Indirect light diffusing system emits an intense and constant level of signal light via a multi-tiered reflector throughout the lens.



S125L LED Steady/ Flashing Signal Light

- Ø125mm LED steady/ flashing signal light
- Shock and vibration-resistant and easy maintenance with long-lasting LED light source
- Built-in switch for selection between steady and flashing mode
- Built-in buzzer type available (Volume : Max 90dB at 1m)
- Flashing rate : 60-80 flashes/min
- Material : Lens - AS, Housing - ABS, Reflector - Heat resistant ABS
- Ambient operating temperature : -30°C to +50°C
- Protection rating : IP44
- Certificates : KIMM, CE Compliant
- Compliant with RoHS directive




Specifications

Model number	Voltage	Current	Certificates	Weight	Color
S125L	DC12V	0.300A	 DC only	0.33kg	• R-Red • A-Amber • G-Green • B-Blue
	DC24V	0.200A		0.33kg	
	AC110V	0.060A		0.51kg	
	AC220V	0.030A		0.51kg	



Technical Diagram

(Units : mm)



Wiring Instructions

- External power line standard : UL1015 AWG18(0.75sq)×2C 400mm
- Product can be wired regardless of polarity



Customization

- 2 buzzer sound types : Both prolonged (beep, beep) and staccato (beep, beep, beep) buzzer output available
- Wall mount bracket options :
Bracket structure allows for threading through the bracket hole or into the wall mount



Wall Mount Bracket
SWP125



Wall Mount Bracket
SWM125



Ordering Specification

S125L	BZ	220	R
[Model number]	[Buzzer option]	[Voltage]	[Color]
• S125L	• None • No buzzer • BZ • Built-in buzzer	• 12-DC12V • 24-DC24V • 110-AC110V • 220-AC220V	• R-Red • A-Amber • G-Green • B-Blue

