S125 series















S125LR

Common Specifications(S125LR/ S125MLR)

- Ø125mm standard LED revolving warning lights
- · Excellent omni-directional visibility with LED light collecting system and special multifaceted reflector
- Built-in buzzer available(Volume : Max 90dB at 1m)
- Revolving speed: 120-140RPM
- Materials: Lens AS, Housing ABS, Reflector Heat resistant ABS
- Ambient operating temperature : -20°C to +50°C

S125LR LED Revolving Warning Light

- Protection rating : IP44
- · Compliant with RoHS directive


| Model number | Voltage | Current | Certificates | Weight | Color |
|--------------|---------|---------|--------------|--------|--|
| S125LR | DC12V | 0.422A | - | 0.43kg | R-RedA-AmberG-GreenB-Blue |
| | DC24V | 0.266A | | 0.43kg | |
| | AC110V | 0.082A | | 0.66kg | |
| | AC220V | 0.041A | | 0.66kg | |




Technical Diagram

(Units: mm)

Qlightec





Feature of LED revolving warning light

LED revolving warning light has Qlight's distinctive LED light collecting system and special multifaceted reflector allowing excellent omni-directional visibility.

Wiring Instructions

- External power line standard : UL1015 AWG18(0.75sq)×2C 400mm
- DC Type: Black output line is negative(-)

Customization

- 2 buzzer sound types: Both prolonged(beep, beep) and staccato(beep, beep, beep) buzzer output available
- Same design with S125R (Model number: S125RLR)
- Wall mount bracket options : Bracket structure allows for threading through the bracket hole or into the wall mount





SWP125



Wall Mount Bracket SWM125

